



POLYPROPYLENE TWINE technical specification

POLYPROPYLENE TWINE technical specification

BIG SQUARE BALER TWINE UV PROTECTED

TYPES	MASTER EXTREM	MASTER	PP 130	PP 150
Linear strength	450 kg	410 kg	360 kg	330 kg
Knot strength	300 kg	245 kg	215 kg	200 kg
Weight of spool	11,5 kg	10 kg	9 kg	9 kg
Weight of bale	11,5 kg	10 kg	18 kg (2x9 kg)	18 kg (2x9 kg)
Bales per pallet	72	72	56	56
Pallet weight	828 kg	720 kg	1008 kg	1008 kg
Pallet size	110 x 120 x 230	85 x 113 x 200	115 x 115 x 220	
Colour	green	beige	white, blue, terracota, black	

BALER TWINE UV PROTECTED

TYPES	PP 350	PP 400	PP 500	
Linear strength	142 kg	126 kg	95 kg	
Weight of spool	5 kg	5 kg	5 kg	
Weight of bale	10 kg (2x5 kg)	10 kg (2x5 kg)	10 kg (2x5 kg)	
Bales per pallet	80	80	80	
Pallet weight	800 kg	800 kg	800 kg	
Pallet size	85 x 113 x 220			
Colour	white, blue, terracota, black			

ROUND BALER TWINE UV PROTECTED

TYPES	PP 600	PP 750	PP 850	PP 1000
Linear strength	84 kg	70 kg	63 kg	54 kg
Weight of spool	5 kg	5 kg	5 kg	5 kg
Weight of bale	10 kg (2x5 kg)	10 kg (2x5 kg)	10 kg (2x5 kg)	10 kg (2x5 kg)
Bales per pallet	80	80	80	80
Pallet weight	800 kg	800 kg	800 kg	800 kg
Pallet size	85 x 113 x 220			
Colour	white, blue, terracota, black			

HORTI TWINE UV PROTECTED

twine can be used for maximum 1 year (1 season)

TYPES	HORTI TWINE 1000	HORTI TWINE 1200	HORTI TWINE 1400	
Linear strength	36 kg	30 kg	25 kg	
Weight of spool	2 kg, 5 kg, 6kg, 10 kg			
Pallet size	85 x 113 x 220			
Colour	white, blue, terracota, black			



CONTACTS:

WWW.JUTA-HOLLAND.NL